

C10X/BU/WS/VC

CEILING MOUNTED

8" O.D. Loudspeaker with a 10 oz. Magnet, 5W-25/70V Transformer, Stud-Mount Baffle, Volume Control



GENERAL DESCRIPTION

The C10X/BU/WS/VC consists of an 8C10PAX - 8" O.D. dual cone loudspeaker with a 10 oz. magnet, TBLU - 5W-25/70V transformer with a screwdriver or knob adjusted (knob is included) volume control, and a BR8WS - round, stud-mount baffle in a white powder coat finish.

INTENDED USE - Indoor Environment

Program Material | Signal tones, voice, and music

AUDIO SPECIFICATIONS

Average Sensitivity	95 dB SPL, 1W/ 1M
Loudspeaker Power Rating	12W RMS, EIA 426A Standard
Maximum Power Rating	15W @ 8 Ohms
Calculated Output	102 dB SPL, 5W/ 1M
Magnet Type & Weight	BeFe Ceramic, 5 oz. Nominal
Frequency Response	65 Hz - 17 kHz EIA 426A Standard
Nominal Coverage Angle	100° Included Angle, -6 dB / 2 kHz, Half space
Audio Connection	7" Color-Coded Leads
Wattage Taps	0.31W, 0.63W, 1.25W, 2.50W, 5W

RECOMMENDED QUAM COMPONENTS

Enclosures	ERD-8, ERD8U
Mounting Device	SSB-2, SSB-3, SSB-7

