# **ATTENUATORS**



# OC10RM

#### **RACK MOUNT**

UL Listed, 20 Watt, 10-Step

# **GENERAL DESCRIPTION**

The **QC10RM** is a UL Listed, rack mount, 20W, ten-step, continuous rotary, audio level attenuator with an OFF position and a black knob with white indicator mark. 2" x 2" dial scale label for a 2RU rack panel is included. Legend is white on black.

# **INTENDED USE - Indoor Environment**

**Primary Use** Attenuates audio power to any number of

loudspeakers, up to 20W load. For use with 25V or

70V distributed audio systems.

UL LISTED 813 Commercial Audio When installed in accordance with supplied instructions and connected to supply circuits in accordance with ANSI/NFPA70, NEC, and AHJ.

Equipment Installation

2RU rack panel or greater, 1/8" maximum thickness



# **AUDIO SPECIFICATIONS**

Power Rating | 20W Continuous

Attenuation

Position 10 : Full Signal Position 9-3 : -3dB each

Position 2-1 : -6 dB each


Position 0 : No Signal


< 0.5 dB

Insertion Loss

(Ref: 25V, 70.7V Line)

Audio Connection 10" long, pre-cut, color coded leads





Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the QUAM Architects' and Engineers' Resources section on the web at: www.QuamSpeakers.com







